

HINDUSTHAN SPECIALITY CHEMICALS LIMITED (An enterprise of The HINDUSTHAN GROUP)

(Technical data sheet)

Hardener HSC 8301

(Medium Curing Phenalkamines)

Product Description	HSC 8301 is a light coloured, low viscosity phenalkamines form cashew nut shell liquid. It can able to cure modified and unmodified epoxy resin at room temperature as well as low temperatures up to 5°C. It is able to demonstrate good curing characteristic in presence of moisture and high humid conditions.	
Features	 Good chemical resistance to acids and alkalis. excellent adhesion & film forming ability on variety of substrates. Moisture sensitive. 	
Applications	 Primers Paints Marine & Industrial coatings	

Product Specifications

Properties	Units	Reference Standard	Value
Appearance	Visual	HTP-1	Yellow Brown liquid
Color	Gardener	ASTM D1544	14 Max
Viscosity @ 25°C	mPas	ASTM D2196	2000-5000
Amine value	Mg KOH/gm	ASTM D2073	300-350
Mix Properties	Units	Reference	Value

Mix Properties	Units	Standard	value
Mix ratio with Epoxy Resin of EEW~185	Pbw	NA	100:67
Pot life (100gm) @ 25 °C	Minutes	ASTM D2471	50-65
Minimum Application Temperature HTP: HSCL Testing Procedure NA: Not Applicable	°C	NA	15

Processing and Storage

HSC 8301 available in bulk packing of drums in packing size of 200 kg and Packing 1000 kg IBC.

Safety & Following instructions needs to be followed strictly. Handling



	 a. Keep working conditions clean. Allow fresh air in, if possible, provide ventilator. b. Avoid contact with human body directly, wear gloves and other personal protective equipment. c. Wash hands carefully with soap. If possible, wash with acetone and alcohol first, then soap and water. d. In case of eye contact, wash with running water for 15 minutes and then seek medical treatment.
	Refer MSDS for better instruction on Safety & Handling.
Storage Conditions	HSC 8301 should be stored in a cool and dry place, preferably in a sealed container and should not be exposed to direct sunlight. This product has a shelf-life of 1 year, if stored in its original container between 18°C and 25°C away from humidity and excessive heat.

Disclaimer	All recommendations for use of our products, whether given by us in
	writing, verbally or to be implied from results of tests carried out by us are
	based on the current state of our knowledge. Notwithstanding any such
	recommendations the Buyer shall remain responsible for satisfying himself
	that the products as supplied by us are suitable for his intended process or
	purpose. Since we cannot control the application, use or processing of the
	products, we cannot accept responsibility. Therefore, the Buyer shall ensure
	that the intended use of the products will not infringe any third party's
	intellectual property rights. We warrant that our products are free from
	defects in accordance with and subject to our general conditions of supply.

Marketing & Sales Office

Hindusthan Speciality Chemicals Limited

65, Free Press House, Free Press Journal Road, Nariman Point, Mumbai – 400021 Tel: +91 22 61510960 Email- <u>sales.hscl@hindusthan.co.in</u>

Works

Hindusthan Speciality Chemicals Limited Plot No.:830, GIDC, Jhagadia Industrial Estate, Jhagadia, Bharuch District, Gujarat – 393110, India Website: www.hindusthanspeciality.com

Page 2 of 2